

BRAKE SPECIFICATIONS

MAZDA 323, 626, 929, MIATA, MILLENIA, MX3, MX6, PROTEGÉ, RX-7

All measurements in inches unless noted

Year	Model		Brake Disc			Brake Drum			Brake Caliper			
			Original Thickness	Minimum Thickness	Maximum Runout	Original Inside Diameter	Max. Wear Limit	Maximum Machine Diameter	Minimum Lining Thickness	Bracket Bolts (ft. lbs.)	Mounting Bolts (ft. lbs.)	
1996	626	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	—	—	—	9.000	—	9.060	0.040	—	—	
	626 w/rear disc	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	0.390	0.310	0.002	—	—	—	0.040	33-49	25-29	
	Miata	F	0.740	0.710	0.002	—	—	—	0.040	36-51	58-65	
		R	0.350	0.310	0.002	—	—	—	0.040	34-49	U35-L27	
	Millenia	F	1.100	1.024	0.004	—	—	—	0.080	76-101	47-62	
		R	0.370	0.295	0.004	—	—	—	0.080	—	37-50	
	MX6	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	—	—	—	9.000	—	9.060	0.040	—	—	
	MX6 w/rear disc	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	0.390	0.310	0.002	—	—	—	0.040	33-49	25-29	
	Protege	F	0.866	0.787	0.002	—	—	—	0.039	—	29-36	
		R	—	—	—	7.874	—	7.933	0.039	—	—	
Protege w/rear disc	F	0.866	0.787	0.002	—	—	—	0.039	—	29-36		
	R	0.354	0.276	0.002	—	—	—	0.039	33-44	33-44		
1997	626	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	—	—	—	9.000	—	9.060	0.040	—	—	
	626 w/rear disc	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	0.390	0.310	0.002	—	—	—	0.040	33-49	25-29	
	Miata	F	0.740	0.710	0.002	—	—	—	0.040	36-51	58-65	
		R	0.350	0.310	0.002	—	—	—	0.040	34-49	U35-L27	
	Millenia	F	1.100	1.024	0.004	—	—	—	0.080	76-101	47-62	
		R	0.370	0.295	0.004	—	—	—	0.080	—	37-50	
	MX6	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	—	—	—	9.000	—	9.060	0.040	—	—	
	MX6 w/rear disc	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	0.390	0.310	0.002	—	—	—	0.040	33-49	25-29	
	Protege	F	0.866	0.787	0.002	—	—	—	0.039	—	29-36	
		R	—	—	—	7.874	—	7.933	0.039	—	—	
Protege w/rear disc	F	0.866	0.787	0.002	—	—	—	0.039	—	29-36		
	R	0.354	0.276	0.002	—	—	—	0.039	33-44	33-44		
1998	626	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	—	—	—	9.000	—	9.060	0.040	—	—	
	626 w/rear disc	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	0.390	0.310	0.002	—	—	—	0.040	33-49	25-29	
	Miata	F	0.740	0.710	0.002	—	—	—	0.040	36-51	58-65	
		R	0.350	0.310	0.002	—	—	—	0.040	34-49	U35-L27	
	Millenia	F	1.100	1.024	0.004	—	—	—	0.080	76-101	47-62	
		R	0.370	0.295	0.004	—	—	—	0.080	—	37-50	
	Protege	F	0.866	0.787	0.002	—	—	—	0.039	—	29-36	
		R	—	—	—	7.874	—	7.933	0.039	—	—	
	Protege w/rear disc	F	0.866	0.787	0.002	—	—	—	0.039	—	29-36	
		R	0.354	0.276	0.002	—	—	—	0.039	33-44	33-44	
	1999-00	626	F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36
			R	—	—	—	9.000	—	9.060	0.040	—	—
626 w/rear disc		F	0.940	0.870	0.002	—	—	—	0.080	58-72	33-36	
		R	0.390	0.310	0.002	—	—	—	0.040	33-49	25-29	