

CAPACITIES

Year	Model	Engine	Engine	Engine	Transmission		Drive Axle		Fuel	Cooling
		Displacement	Engine	Oil with	(pts.)		Front	Rear	Tank	System
		Liters (cc)	ID/VIN	Filter	5-Spd	Auto.	(pts.)	(pts.)	(gal.)	(qts.)
1999-00	626 ES	2.0 (1991)	FS	4.0	6.0	17.6	①	—	16.9	7.9
	626 ES-V6	2.5 (2497)	KL	4.2	6.0	17.0	①	—	16.9	7.9
	626 LX	2.0 (1991)	FS	4.0	6.0	17.6	①	—	16.9	7.9
	626 LX-V6	2.5 (2497)	KL	4.2	6.0	17.0	①	—	16.9	7.9
	Miata	1.8 (1839)	BP	4.0	4.2	13.5	①	2.1	12.7	6.3
	Millenia	2.5 (2497)	KL	5.2	—	16.9	①	—	18.0	7.4
	Millenia S	2.3 (2255)	KJ	5.9	—	16.9	①	—	18.0	7.4
	Protege DX	1.6 (1597)	ZM	5.0	5.6	15.2	①	—	13.2	7.9
	Protege ES	1.8 (1839)	FP	5.0	5.6	15.2	①	—	13.2	9.9
Protege LX	1.6 (1597)	ZM	5.0	5.6	15.2	①	—	13.2	7.9	

NOTE: All capacities are approximate. Add fluid gradually and check to be sure a proper fluid level is obtained.

- | | |
|---|---|
| ① Included in transaxle | ⑧ 2WD: 5.6 pts.
4WD: 5.4 pts. |
| ② Manual trans.: 5.3 qts.
Automatic trans.: 6.3 qts. | ⑨ 2WD: 12.2 pts.
4WD: 14.0 pts. |
| ③ Non-turbocharged engine: 7 pts.
Turbocharged engine: 7.8 pts. | ⑩ 2WD: 14.5 gal.
4WD: 15.8 gal. |
| ④ With 4-wheel steering: 15 gal.
Without 4-wheel steering: 15.9 gal. | ⑪ With heater: 9.9 qts.
Without heater: 9.3 qts. |
| ⑤ With heater: 7.9 qts.
Without heater: 7.4 qts. | ⑫ Except RI package: 5.2 qts.
RI package: 5.7 qts. |
| ⑥ Except Turbo engine with limited slip: 2.8 pts.
Turbo engine with limited slip: 3.0 pts. | |
| ⑦ Non-turbo engine: 7.7 qts.
Turbo engine: 9.2 qts. | |